PREDICTED ENERGY ASSESSMENT



Foundland, Plot 78, Phase 4 A, Tarland Road, Aboyne Dwelling type: Date of assessment: Produced by: Total floor area: House, Detached 11/03/2024 Northern Energy 162.55 m²

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP2012 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO_2) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

Environmental Impact (CO₂) Rating



The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO_2) emissions. The higher the rating the less impact it has on the environment.

This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.



Regs Region: Scotland Elmhurst Energy Systems SAP2012 Calculator (Design System) version 4.14r19

BUILDING REGULATION COMPLIANCE Calculation Type: New Build (As Designed)



| Property Reference | ajc 4A 78 foundland | | | | Issued on Date | 11/03/2024 | |
|--|--|---|--|------------|-----------------------------------|------------|--|
| Assessment | Foundland | Prop Type Ref | | | | | |
| Reference | | | | | | | |
| Property Foundland, Plot 78, Phase 4 A, Tarland Road, Aboyne | | | | | | | |
| SAP Rating | | 82 B | DER | 11.22 | TER | 12.48 | |
| Environmental | | 89 B | % DER <ter< th=""><th></th><th>10.10</th><th></th></ter<> | | 10.10 | | |
| CO ₂ Emissions (t/year) | | 2.03 | FEE | 49.32 | TFEE | N/A | |
| General Requiremen | ts Compliance | Pass | % DFEE <tfee< th=""><th></th><th>N/A</th><th></th></tfee<> | | N/A | | |
| Assessor Details | Mr. William MacDougall, Nor n.energy@btinternet.com | thern Energy, | Tel: 019755 81400 |), | Assessor ID | 1910-0001 | |
| Client | | | | | | | |
| SUMARY FOR INPUT DATA FOR New Build (As Designed) | | | | | | | |
| 6.1 Carbon Dioxide Er | nissions | | | | | | |
| <u>1a TER and DER</u> | | | | | | | |
| Fuel for main heat | Bulk LPG | Bulk LPG | | | | | |
| Fuel package for TER | | LPG | | | | | |
| Target Carbon Dioxide Emission Rate (TER) | | 12.48 | | | kgCO ₂ /m ² | | |
| Dwelling Carbon Dioxide Emission Rate (DER) | | 11.22 | 11.22 kgCO ₂ /m ² | | | | |
| | | -1.26 (-1 | 0.1%) | | kgCO ₂ /m ² | | |
| 6.2 Building insulation | n envelope | | | - | | | |
| 2 Fabric U-values | | | | , | | | |
| Element | Average | | Highe | est | | | |
| External wall | 0.17 (ma | x. 0.22) | 0.20 (| max. 0.70) | | Pass | |
| Floor | 0.12 (ma | x. 0.18) | 0.15 (| max. 0.70) | | Pass | |
| Root | 0.11 (ma | x. 0.15) | 0.15 (| max. 0.35) | | Pass | |
| Openings 1.39 (max. 1.60) | | | 1.40 (| max. 3.30) | | Pass | |
| 2a Thermal bridging | | | | | | | |
| Thermal bridging o | calculated from linear therma | I transmittanc | es for each junctio | on | | | |
| <u>3 Air permeability</u> | | 4.00 (design value) | | | | | |
| All permeability at | . So pascais | 4.00 (ue: | sign value) | | | | |
| 4 Heating efficiency | | | | | | | |
| Main heating syste | Boiler sv | Boiler system with radiators or underfloor - Bulk LPG | | | | | |
| Wain nearing system | | Data from database | | | | 1 435 | |
| | | Baxi ASSURE 18 SYSTEM LPG | | | | | |
| | | | Efficiency: 90.2% SEDBLIK2009 | | | | |
| | | Minimum: 88.0% | | | | | |
| Secondary heating system | | None | None | | | | |
| <u>6 Controls</u> | | | | | | | |
| Space heating con | trols | Time and | d temperature zon | e control | | Pass | |
| Hot water controls | | Cylinders | Cylinderstat | | | | |
| | • | Indepen | dent timer for DH\ | N | | Pass | |
| Boiler interlock | | Yes | Yes | | | | |
| 6.4 Insulation of pipe | 6.4 Insulation of pipes, ducts and vessels | | | | | | |
| | | | | | | | |



Regs Region: Scotland Elmhurst Energy Systems SAP2012 Calculator (Design System) version 4.14r19

BUILDING REGULATION COMPLIANCE Calculation Type: New Build (As Designed)



| 5 Cylinder insulation | | |
|---|--------------------------------------|------|
| Hot water storage | Measured cylinder loss: 2.22 kWh/day | Pass |
| | Permitted by DBSCG 2.56 | |
| Primary pipework insulated | Yes | Pass |
| 6.5 Artificial and display lighting | | |
| 7 Low energy lights | | |
| Percentage of fixed lights with low-energy fittings | 100 % | |
| Minimum | 75 % | Pass |
| 6.6 Mechanical ventilation and air conditioning | | |
| 8 Mechanical ventilation | | |
| Continuous extract system (decentralised) | | |
| Specific fan power | 0.1600 0.2000 | |
| Maximum | 0.7 | Pass |
| 9 Summertime temperature | | |
| Overheating risk (North Fast Scotland) | Not significant | Pass |
| Based on: | | |
| Overshading | Average | |
| Windows facing North | 7.74 m ² . No overhang | |
| Windows facing East | 5.25 m ² , No overhang | |
| Windows facing South | 12.61 m ² , No overhang | |
| Windows facing West | 4.77 m ² , No overhang | |
| Air change rate | 2.50 ach | |
| Blinds/curtains | None | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| ▼ | | |



RECOMMENDATIONS





This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.



Regs Region: Scotland Elmhurst Energy Systems SAP2012 Calculator (Design System) version 4.14r19